

VIKING TOTALPAC3 UNITS

CONFIGURATION / ORDER FORM

Note: This form **MUST** accompany each order sent to your TOTALPAC3 Authorized Distributor

Date:		Purchase Order No.:	
Company Name:		SHIP TO:	
Address:			
State/Prov.:	Zip/Postal Code:	State/Prov.:	Zip/Postal Code:
Buyer's Name:		Notes:	
Project name:			
Engineer:		Quantity (see note):	

NOTE: Unless they are all the same, use one Configuration / Order Form per system size and / or type when ordering multiple units.
INSTRUCTIONS: First, select the system type. Then, choose the style of system required and its release system. Finally, select the proper system by circling the part number under the column of the system size. This is the item you will order from your local SupplyNet office. Add the required system options to complete your order and sign at the bottom of the last page.

SYSTEM TYPE	STYLE	RELEASE	SYSTEM SIZE						
			1½"	2"	3"	4"	6"	8"	
PREACTION SYSTEMS Specify pressure adjustment: <input type="checkbox"/> 175 psi <input type="checkbox"/> 250 psi									
<input type="checkbox"/> PREACTION NON INTERLOCK	Skid Mounted	Electric	T3PNELSK15	T3PNELSK20	T3PNELSK30	T3PNELSK40	T3PNELSK60	N/A	
		Pneumatic	T3PNPNSK15	T3PNPNSK20	T3PNPNSK30	T3PNPNSK40	T3PNPNSK60	N/A	
	Without Panel (Remote)	Electric	T3PNELNP15	T3PNELNP20	T3PNELNP30	T3PNELNP40	T3PNELNP60	T3PNELNP80	
		Pneumatic	T3PNPNNP15	T3PNPNNP20	T3PNPNNP30	T3PNPNNP40	T3PNPNNP60	T3PNPNNP80	
	With VFR-400	Electric	T3PNELWP15	T3PNELWP20	T3PNELWP30	T3PNELWP40	T3PNELWP60	T3PNELWP80	
<input type="checkbox"/> PREACTION SINGLE INTERLOCK	Skid Mounted	Electric	T3PSELSK15	T3PSELSK20	T3PSELSK30	T3PSELSK40	T3PSELSK60	N/A	
		Pneumatic	T3PSPNSK15	T3PSPNSK20	T3PSPNSK30	T3PSPNSK40	T3PSPNSK60	N/A	
	Without Panel (Remote)	Electric	T3PSELNP15	T3PSELNP20	T3PSELNP30	T3PSELNP40	T3PSELNP60	T3PSELNP80	
		Pneumatic	T3PSPNNP15	T3PSPNNP20	T3PSPNNP30	T3PSPNNP40	T3PSPNNP60	T3PSPNNP80	
	With VFR-400	Electric	T3PSELWP15	T3PSELWP20	T3PSELWP30	T3PSELWP40	T3PSELWP60	T3PSELWP80	
<input type="checkbox"/> PREACTION DOUBLE INTERLOCK Note: NYFD Accepted & FM Approved for use in refrigerated areas only.	Skid Mounted	Elect-Pneumatic	T3PDEPSK15	T3PDEPSK20	T3PDEPSK30	T3PDEPSK40	T3PDEPSK60	N/A	
		Elect-Pneumatic	T3PDPASK15	T3PDPASK20	T3PDPASK30	T3PDPASK40	T3PDPASK60	N/A	
		Pneum-Pneumatic	T3PDPPSK15	T3PDPPSK20	T3PDPPSK30	T3PDPPSK40	T3PDPPSK60	N/A	
	Without Panel (Remote)	Elect-Pneumatic	T3PDEPNP15	T3PDEPNP20	T3PDEPNP30	T3PDEPNP40	T3PDEPNP60	T3PDEPNP80	
		Elect-Pneumatic	T3PDPANP15	T3PDPANP20	T3PDPANP30	T3PDPANP40	T3PDPANP60	T3PDPANP80	
		Pneum-Pneumatic	T3PDPPNP15	T3PDPPNP20	T3PDPPNP30	T3PDPPNP40	T3PDPPNP60	T3PDPPNP80	
	With VFR-400	Elect-Pneumatic	T3PDEPWP15	T3PDEPWP20	T3PDEPWP30	T3PDEPWP40	T3PDEPWP60	T3PDEPWP80	
		Elect-Pneumatic	T3PDPAWP15	T3PDPAWP20	T3PDPAWP30	T3PDPAWP40	T3PDPAWP60	T3PDPAWP80	
	DELUGE SYSTEMS Specify pressure adjustment: <input type="checkbox"/> 175 psi <input type="checkbox"/> 250 psi								
	<input type="checkbox"/> DELUGE	Skid Mounted	Electric	T3DEELSK15	T3DEELSK20	T3DEELSK30	T3DEELSK40	T3DEELSK60	N/A
			Pneumatic	T3DEPNSK15	T3DEPNSK20	T3DEPNSK30	T3DEPNSK40	T3DEPNSK60	N/A
Hydraulic			T3DEHYSK15	T3DEHYSK20	T3DEHYSK30	T3DEHYSK40	T3DEHYSK60	N/A	
Without Panel (Remote)		Electric	T3DEELNP15	T3DEELNP20	T3DEELNP30	T3DEELNP40	T3DEELNP60	T3DEELNP80	
		Pneumatic	T3DEPNNP15	T3DEPNNP20	T3DEPNNP30	T3DEPNNP40	T3DEPNNP60	T3DEPNNP80	
		Hydraulic	T3DEHYNP15	T3DEHYNP20	T3DEHYNP30	T3DEHYNP40	T3DEHYNP60	T3DEHYNP80	
With VFR-400		Electric	T3DEELWP15	T3DEELWP20	T3DEELWP30	T3DEELWP40	T3DEELWP60	T3DEELWP80	

SYSTEM TYPE	STYLE	RELEASE	SYSTEM SIZE					
			1½"	2"	3"	4"	6"	8"
WET PIPE SYSTEMS 175 psi only								
<input type="checkbox"/> WET PIPE	Skid Mounted	N/A	N/A	N/A	T3WETESK30	T3WETESK40	T3WETESK60	N/A
	In Cabinet	N/A	N/A	N/A	T3WETENP30	T3WETENP40	T3WETENP60	T3WETENP80
	SYSTEM OPTIONS							
	Retard Chamber	T3WETRET00						
	Excess Pressure Pump	1/3 HP T3WETEPP00			1/2 HP T3WETEPP01			
DRY PIPE SYSTEMS								
<input type="checkbox"/> DRY PIPE 175 psi	Skid Mounted	N/A	N/A	N/A	N/A	T3DRYESK40	T3DRYESK60	N/A
	In Cabinet (Remote)	N/A	N/A	N/A	N/A	T3DRYENP40	T3DRYENP60	N/A
<input type="checkbox"/> HP DRY PIPE 250 psi	Skid Mounted	N/A	T3DHPESK15	T3DHPESK20	T3DHPESK30	T3DHPESK40	T3DHPESK60	N/A
	In Cabinet (Remote)	N/A	T3DHPENP15	T3DHPENP20	T3DHPENP30	T3DHPENP40	T3DHPENP60	N/A
MULTI-CYCLE SYSTEMS Specify pressure adjustment: <input type="checkbox"/> 175 psi <input type="checkbox"/> 250 psi								
<input type="checkbox"/> PREACTION SINGLE INTERLOCK	Skid Mounted	Firecycle III	T3FSINSK15	T3FSINSK20	T3FSINSK30	T3FSINSK40	T3FSINSK60	N/A
	Without Panel (Remote)		T3FSINNP15	T3FSINNP20	T3FSINNP30	T3FSINNP40	T3FSINNP60	T3FSINNP80
	With VFR-400		T3FSINWP15	T3FSINWP20	T3FSINWP30	T3FSINWP40	T3FSINWP60	T3FSINWP80
<input type="checkbox"/> PREACTION DOUBLE INTERLOCK	Skid Mounted	Firecycle III	T3FDOSK15	T3FDOSK20	T3FDOSK30	T3FDOSK40	T3FDOSK60	N/A
	Without Panel (Remote)		T3FDOUNP15	T3FDOUNP20	T3FDOUNP30	T3FDOUNP40	T3FDOUNP60	T3FDOUNP80
	With VFR-400		T3FDOWP15	T3FDOWP20	T3FDOWP30	T3FDOWP40	T3FDOWP60	T3FDOWP80
<input type="checkbox"/> DELUGE	Skid Mounted	Firecycle III	T3FDELSK15	T3FDELSK20	T3FDELSK30	T3FDELSK40	T3FDELSK60	N/A
	Without Panel (Remote)		T3FDELNP15	T3FDELNP20	T3FDELNP30	T3FDELNP40	T3FDELNP60	T3FDELNP80
	With VFR-400		T3FDELWP15	T3FDELWP20	T3FDELWP30	T3FDELWP40	T3FDELWP60	T3FDELWP80
<input type="checkbox"/> WET PIPE	Skid Mounted	Firecycle III	T3FWETSK15	T3FWETSK20	T3FWETSK30	T3FWETSK40	T3FWETSK60	N/A
	Without Panel (Remote)		T3FWETNP15	T3FWETNP20	T3FWETNP30	T3FWETNP40	T3FWETNP60	T3FWETNP80
	With VFR-400		T3FWETWP15	T3FWETWP20	T3FWETWP30	T3FWETWP40	T3FWETWP60	T3FWETWP80
SUREFIRE PREACTION SYSTEMS: Specify pressure adjustment: <input type="checkbox"/> 175 psi <input type="checkbox"/> 250 psi								
<input type="checkbox"/> PREACTION SINGLE INTERLOCK	Skid Mounted	Surefire	T3SFSISK15	T3SFSISK20	T3SFSISK30	T3SFSISK40	T3SFSISK60	N/A
	Without Panel (Remote)		T3SFSINP15	T3SFSINP20	T3SFSINP30	T3SFSINP40	T3SFSINP60	T3SFSINP80
	With VFR-400		T3SFSIWP15	T3SFSIWP20	T3SFSIWP30	T3SFSIWP40	T3SFSIWP60	T3SFSIWP80
<input type="checkbox"/> PREACTION DOUBLE INTERLOCK see note	Skid Mounted	Surefire	T3SFDOSK15	T3SFDOSK20	T3SFDOSK30	T3SFDOSK40	T3SFDOSK60	N/A
	Without Panel (Remote)		T3SFDONP15	T3SFDONP20	T3SFDONP30	T3SFDONP40	T3SFDONP60	T3SFDONP80
	With VFR-400		T3SFDOWP15	T3SFDOWP20	T3SFDOWP30	T3SFDOWP40	T3SFDOWP60	T3SFDOWP80

Note: NYFD Accepted & FM Approved for use in refrigerated areas only.

SYSTEM TRIM OPTIONS	SYSTEM SIZE					
	1½"	2"	3"	4"	6"	8"
Shut-off Valve & Sight Glass (Not available for Wet & Dry Pipe systems)	T3SHUTV015	T3SHUTV020	T3SHUTV030	T3SHUTV040	T3SHUTV060	N/A
Fire Department Connection (Always on right hand side)	T3FIRDPT15	T3FIRDPT20	T3FIRDPT30	T3FIRDPT40	T3FIRDPT60	N/A
Semi-Flanged Inlets & Outlet: Inlet: <input type="checkbox"/> L <input type="checkbox"/> R Drain: <input type="checkbox"/> L <input type="checkbox"/> R	T3SEMFLG15	T3SEMFLG20	T3SEMFLG30	T3SEMFLG40	T3SEMFLG60	T3SEMFLG80
Full-Flanged Inlets & Outlet: Only available on request in 4" dia. – Check with FireFlex Systems for details and availability.						
Galvanized Main Inlet & Riser Option	T3GALVOPT1					
Elevator Option (not approved)	T3ELEVATOR					
ANTI Column device	T3ANTCOLD1					
OSHPD Seismic Option	T3SISMIQ00					

VFR-400 CONTROL PANEL OPTIONS			Specify voltage: <input type="checkbox"/> 120V / 60Hz <input type="checkbox"/> 220V / 50Hz
Zones Programming:	<input type="checkbox"/> Single Zone (Zone 1 OR Zone 2)	<input type="checkbox"/> Crossed Zones (Zone 1 AND Zone 2)	
Firecycle III Soaking Timer Adjustment:	<input type="checkbox"/> _____ Sec. (Available 30, 60, 90 sec. & from 2 to 20 min. in 1 min. increments)		
Emergency Batteries:	Standard Systems:	7 AH batteries (included with the standard system) T3BAT02407	<input type="checkbox"/> 12 AH (FM's 90 Hrs Stand-by) T3BAT02412
	Surefire & Firecycle III Systems:	12 AH (Included with unit) T3BAT02412	<input type="checkbox"/> 18 AH (FM's 90 Hrs Stand-by) T3BAT02418
VFR-400 Panel Options:	<input type="checkbox"/> Remote Annunciator Panel T3VFRP4410 Qty: _____	<input type="checkbox"/> Class "A" (Style Z) Indicating Circuits T3VFRPCAM2 Qty: _____	<input type="checkbox"/> Class "A" (Style D) Initiating Circuits T3VFRPCA2Z Qty: _____
	<input type="checkbox"/> NYFD Kit (Incl. Class A Mods) T3VFRPNYOP	<input type="checkbox"/> Relay Module T3OPTARM44	
Note: VFR-400 panel provides 4 sets of dry contacts. When additional dry contacts are required, use Viking p/n MR-101 (SPDT), MR-201 (DPDT) and / or MR-801 (SPDT with LED). These field devices shall be installed OUTSIDE the TotalPac3 enclosure. Contact your local Viking SupplyNet representative for pricing and availability.			
<input type="checkbox"/> Los Angeles City Auxiliary Contacts T3LAOPTION		<input type="checkbox"/> Chicago City Auxiliary Contacts T3CHOPTION	
Note: The Los Angeles and Chicago City Auxiliary Contacts options are also available for remote units.			

AIR SUPPLIES									
Air Supplies for Skids (Trim only)	External air for sprinkler piping <small>For Preaction – Surefire, Firecycle III, Dry & HP Dry Pipe</small>			Pilot line only <small>For System with Pneumatic Release</small>			External air for sprinkler piping & pilot line <small>Non orSingle Int'l'k with Pneum. & Double Int'l'k Pneum-Pneum</small>		
	T3ARTITSK1			T3ARTITSK2			T3ARTITSK3		
Air Supplies for Cabinets	Style "A" (Tankless Air Compressor)						Style "B" Air Pressure Maintenance Device for Sprinkler Piping	Style "C" Air Pressure Maintenance Device for Pilot Line	Style "D" Air Shut-off Valve, Pressure Gauge, & Pressure Switch Only
	Size:	1/6 HP	1/3 HP	1/2 HP	1 HP	1 ½ HP (8" unit only)			
<input type="checkbox"/> 120 V/ 60 Hz <input type="checkbox"/> 220 V/ 60 Hz	T3AIRK0A02	T3AIRK0A03	T3AIRK0A05	T3AIRK0A10	T3AIRK0A15	T3AIRK0A20			
220V / 50 Hz:	T3AIRK2A02	T3AIRK2A03	T3AIRK2A05	T3AIRK2A10	T3AIRK2A15	N/A	T3AIRK0B00	T3AIRK0C00	T3AIRK0D00
Notes:									
1. Style "A" Air Supply cannot be mixed with Style "B".									
2. In the case of a Preaction System with Pilot Line, order either one Style "A" with one Style "C" if you need a tankless air compressor in the cabinet for the sprinklers piping, OR, one Style "B" and one Style "C" if you want both air supplies to be located outside the system cabinet.									
3. Pilot Line Air Supply will always be provided by a source located outside the TotalPac3 Cabinet, supplied by others (not FireFlex Systems).									
4. Air Supply Style "D" is used when air supply and regulation is provided by others, as is the case with plant air, or with refrigerated areas when a dry air supply as described in NFPA-13 is required.									
5. 1 HP Air compressor available on 4" & 6" systems only.									
6. 1 ½ HP & 2 HP Air compressors available on 8" systems only.									

AIR SUPPLY OPTIONS		
Accelerator E-1	Without Anti-flood Device (For Preaction, Pneum. Rel. Pilot Line & HP Dry only)	With Anti-flood Device (For Standard Dry Pipe only)
	T3ACCELE1P	T3ACCELE1D
Dehydrator	T3DEHYDRAT	

PRODUCT RETURN POLICY

Special Order Item: TotalPac3 Units are Special Order Items and are built to order. Because of this, delivered units cannot be returned for credit without FireFlex Systems explicit authorization.

The following conditions apply for any TotalPac3 Unit returned to the factory for credit:

- Unit(s) shall be of current design, three months old maximum (after shipping date from the factory);
- Unit(s) shall be in their original packing (never unpacked) and never used. Any unit not returned in this condition is subject to additional charges to cover inspection, handling, repackaging, refurbishment, and any other expenses incurred by FireFlex Systems in accepting the unit(s).
- Minimum restocking fees will apply to every returned unit (contact your TotalPac Authorized Distributor for further details).
- The customer is responsible for return freight charges, FOB our warehouse. Any damage incurred in transit will be deducted from credit value.

Notes: An RMA Number shall be obtained from your TotalPac Authorized Distributor PRIOR to returning any unit. Please provide unit(s) serial number(s) as indicated on the shipping label of the unit(s) (format: TOT3xxxx) as well as the address for us to make arrangements for pick-up.

NOTES

Form completed by: _____